

Command

Primary Yarn Polymer	Polyethylene		
Yarn Cross Section	Mini "C" Shaped Monofilament	Primary Backing	(2) 13 Pic
Standard Color	Field Green/ Olive Green	Coating Type	Polyurethane
Fabric Construction	Tufted	PE Yarn Denier / Ends	8,000/8
Second Yarn Polymer Thatch	Texture Polyethlene	Texturized Thatch Denier	/ Ends 3,600/8
Secondary Yarn Color	Tan/Turf Green	Warranty Period	10 Year

Finish Fabric	English System		ASTM Test
Nominal Specification	Value	Units	Method
ile Height (Nominal)	1	Inches	D-5823
ace Weight	45	oz/yd²	D-5848
otal Fabric Weight	72	oz/yd²	D-5848
Primary Backing Weight	7	oz/yd²	D-5848
Secondary Coating Weight	20	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
otal Yarn Linear Density	11,600	Denler	D-1577
Elongation to Break	> 60	%	0-2256
Yarn Breaking Strength	> 19	lbs.	D-2256
Machine Guage	3/8	Inches	D-5793
Flammability	Passed	14	D-2859
Nater Permeability	>30	In/hr	DIN 18-035
abric Width	12	ft	







Product Specifications



Grass Zone Denier

Grass Zone Yarn/Color

Thatch Zone Yarn/Color

Thatch Zone Denier

Grass Zone Yarn Shape

Finished Pile Height

Finished Pile Weight

Backing

Tuft Gauge

Total Weight

Tuft Bind

Permeability

Features

Test Data

Field Green/Olive Green

8.000/8

Tan/Turf Green

3,600/8

Mini "C" Shape Monofilament

1"

45 oz/yd2

(2) 13 Pic

3/8"

72 oz/yd2

>8 lbs

>30 in/hr

10-Year Warranty, Great 45oz Face Weight, Mini "C" Shaped Fiber, Fire

Rating

ASMT Certified D5823,D5848, D1335, D5034,F2765,D1577, D2256, D7138, D5793, D2859, DIN 18-035

Command has a DuraGrass backing, made from polyurethane, provides durability and dimensional stablilty. The product is perforated to allow maximum drainage over all properly constructed sub-bases.











RECOMMENDED USES









