






Fairway Ultra

The fibers of Fairway Ultra are securely tufted together with texturized polyethylene fibers to provide ballast and tan/turf green colored thatch yarn provides contrasts to the larger face fibers. With its DuraGrass backing, this product is a great choice for your golf course.


Grass Zone Yarn/Color	Field Green/ Olive Green
Grass Zone Denier	8,000/8
Thatch Zone Yarn/Color	Tan/ Turf Green
Thatch Zone Denier	3,6000/8
Grass Zone Yarn Shape	Mini "C" Shape Monofilament
Finished Pile Height	1"
Finished Pile Weight	45 oz/yd ²
Backing	(2) 13 Pic
Tuft Gauge	3/8"
Total Weight	72 oz/yd ²
Tuft Bind	>8 lbs
Permeability	>30 in/hr
Features	10-Year Warranty, Great 45 oz Face Weight, Mini C Shaped Fiber, Fire Rating
Test Data	ASMT Certified D5823, D5848, D1335, D5034, D1335, D5034, F2765, D1577, D2256, DIN 18-035

-  Unmatched Lifetime Warranty
-  EnviroLoc™ Plant-Based Backing
-  Deluster and UV Protection



Not to scale. For illustration only.

RECOMMENDED USES



Primary Yarn Polymer	Polyethylene	Primary Backing	(2) 13 Pic
Yarn Cross Section	Mini "C" Shape Monofilament	Cushion	5mm Padding
Standard Color	Field Green/Olive Green	PE Yarn Denier / Ends	8,000/8
Fabric Construction	Tufted	Texturized Thatch Denier / Ends	3,600/8
Second Yarn Polymer Thatch	Texture Polyethylene	Warranty Period	10 Years
Secondary Yarn Color	Tan/Turf Green		

Finish Fabric	English System		ASTM Test
	Nominal Specification	Value	Units
Pile Height (Nominal)	1	Inches	D-5823
Face Weight	45	oz/yd ²	D-5848
Total Fabric Weight	72	oz/yd ²	D-5848
Primary Backing Weight	7	oz/yd ²	D-5848
Secondary Coating Weight	20	oz/yd ²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	11,600	Denier	D-1577
Elongation to Break	>60	%	D-2256
Yarn Breaking Strength	>19	lbs.	D-2256
Machine Gauge	3/8	Inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	>30	In/hr	DIN 18-035
Fabric Width	12	ft	.

