



In The Ruff

This revolutionary product shows amazingly out of the box packing a whopping 120oz of face fiber for the lushest, most luxurious looking landscape ever. Sure to wow residential and commercial customers, the look and feel are phenomenal.

Grass Zone Yarn/Color	PE / Field Green / Olive / Clover
Grass Zone Denier	9,900 / 9
Thatch Zone Yarn/Color	PE / Field Green / Beige
Thatch Zone Denier	5,000 / 8
Grass Zone Yarn Shape	"S" Shape
Finished Pile Height	2 1/2"
Finished Pile Weight	120 oz.
Backing	15 / 18 PP 2-Part / 20oz. EnviroLoc™
Tuft Gauge	1/2"
Total Weight	146 oz.
Tuft Bind	> 8 lbs.
Permeability	> 400 inches per / SY
Features	EnviroLoc™, HeatBlock™, Deluster, UV Stabilizers
Test Data	ASTM Certified F1292, F1551, F1951



Unmatched Lifetime Warranty



EnviroLoc™ Plant-Based Backing



Deluster and UV Protection



Foot Traffic



Softness




RECOMMENDED USES



LANDSCAPE



PETS



Primary Yarn Polymer	Polyethylene	Primary Backing	15/18 PP 2-Part
Yarn Cross Section	"S" Shape	Coating Type	20 oz. EnviroLoc™
Standard Color	Field Green / Olive / Clover	PE Yarn Denier / Ends	9,900 / 9
Fabric Construction	Tufted	Texturized Thatch Denier / Ends	5,000 / 8
Second Yarn Polymer Thatch	Polyethylene	Warranty Period	Limited Lifetime
Secondary Yarn Color	Field Green / Beige		

Finish Fabric	English System		ASTM Test
	Nominal Specification	Value	Units
Pile Height (Nominal)	2 1/2	Inches	D-5823
Face Weight	120	oz/yd ²	D-5848
Total Fabric Weight	146	oz/yd ²	D-5848
Primary Backing Weight	6	oz/yd ²	D-5848
Secondary Coating Weight	20	oz/yd ²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	14,900	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	1/2	Inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	442.68	In/hr	D-1551
Fabric Width	15	ft	-

