



Premier

Rival to our best selling products combining multi-colored grass and thatch fibers to create an 80-ounce contender, which is both lush and durable. Economically priced without compromising quality make this turf style a real head-turner.

Grass Zone Yarn/Color	PE / Field Green / Clover
Grass Zone Denier	10,800 / 6
Thatch Zone Yarn/Color	PE / Field Green / Beige
Thatch Zone Denier	5,000 / 8
Grass Zone Yarn Shape	'S' Shape
Finished Pile Height	1 7/8"
Finished Pile Weight	80 oz.
Backing	15 / 18 PP 2-Part / 20oz. EnviroLoc™
Tuft Gauge	3/8"
Total Weight	106 oz.
Tuft Bind	> 8 lbs.
Permeability	> 300 inches per / SY
Features	Deluster, UV Stabilizers
Test Data	ASTM Certified F1292, F1551, F1951



Unmatched Lifetime Warranty



EnviroLoc™ Plant-Based Backing



Deluster and UV Protection




Foot Traffic



Softness



RECOMMENDED USES



Primary Yarn Polymer	Polyethylene	Primary Backing	15/18 PP 2-Part
Yarn Cross Section	'S' Shape	Coating Type	20 oz. EnviroLoc™
Standard Color	Field Green / Clover	PE Yarn Denier / Ends	10,800 / 6
Fabric Construction	Tufted	Texturized Thatch Denier / Ends	5,000 / 8
Second Yarn Polymer Thatch	Polyethylene	Warranty Period	Limited Lifetime
Secondary Yarn Color	Field Green / Beige		

Finish Fabric	English System		ASTM Test
	Nominal Specification	Value	Units
Pile Height (Nominal)	1 7/8	Inches	D-5823
Face Weight	80	oz/yd ²	D-5848
Total Fabric Weight	106	oz/yd ²	D-5848
Primary Backing Weight	6	oz/yd ²	D-5848
Secondary Coating Weight	20	oz/yd ²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	15,800	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/8	Inches	D-5793
Flammability	Passed	-	D-2859
Water Permeability	344.31	In/hr	D-1551
Fabric Width	15	ft	-

