



SKU		I

Grass Zone Yarn/Color

Grass Zone Denier

Thatch Zone Yarn/Color

Thatch Zone Denier

Grass Zone Yarn Shape

Finished Pile Height

Finished Pile Weight

Backing **Tuft Gauge** 

Total Weight

Tuft Bind

Permeability

Features

Test Data

Landing Zone

Nylon / Verde

4,200/8

Textured Diamond

3/8"

47 oz.

15/18 PP 2-Part / 20oz. Embossed

3/16"

73 oz.

> 8 lbs.

HeatBlock\*\* **UV Stabilizers** 

ASTM E108 Class A Fire Rating, ASTM E648

## Landing Zone

Improve your game with our best-selling putting green surface, known for its performance and superior ball control. With nylon fibers and an embossed backing, this turf accepts shots like a champ and delivers a 12 on the Stimpmeter.



Unmatched Lifetime Warranty



EnviroLoc Plant-Based Backing



Deluster + UV Protection



## ASK FOR A...







RECOMMENDED USES











## Landing Zone

Primary Yarn Polymer	Nylon	
Yarn Cross Section	Textured Diamond	
Standard Color	Verde	
Fabric Construction	Tufted	
Second Yarn Polymer Thatch	-	
Secondary Yarn Color		

Primary Backing	15/18 PP 2-Part		
Coating Type	20 oz. Embossed		
PE Yarn Denier / Ends	4,200/8		
Texturized Thatch Denier / Ends	-		
Warranty Period	Limited Lifetime		

Finish Fabric	English System		ASTM Test
Nominal Specification	Value	Units	Method
Pile Height (Nominal)	3/8	inches	D-5823
Face Weight	47	oz/yd²	D-5848
Total Fabric Weight	73	oz/yd²	D-5848
Primary Backing Weight	6	oz/yd²	D-5848
Secondary Coating Weight	20	oz/yd²	D-5848
Tuft Bind	> 8	lbs.	D-1335
Grab Tear Strength (Average)	> 200	lbs.	D-5034
Total Yarn Linear Density	4,200	Denier	D-1577
Elongation to Break	> 30	%	D-2256
Yarn Breaking Strength	> 20	lbs.	D-5793
Machine Gauge	3/16	inches	D-5793
Flammability	Passed		D-2859
Water Permeability		in/hr	D-1551
Fabric Width	15	ft	



